

Incubators / COMPRESSOR-COOLED INCUBATORS ICP

Options	Order No.	110	260	450	750
Voltage 115 V, 50/60 Hz	X2		●		●
Chamber modification for the application of reinforced perforated stainless steel shelves or stainless steel grids (bearing rails mounted in the working chamber) - includes replacement of standard grids by reinforced grids	K1	-		●	●
Interior socket, ampacity 230V/2, 2A/500W, can be switched off with the On/Off switch, cannot be switched individually, moisture tight IP68 (max. one per appliance)	R3		●		
Entry port with 23 mm clear diameter, can be closed, standard position	left centre/centre		●		
	left centre/top		●		
	right centre/top	-		●	
Entry port (silicone), 40 mm clear diameter, moisture tight, can be closed by silicone stopper, at the back (please state location)	F7		●		
4 - 20 mA current loop interface	Temperature controller actual value (-20 to +70 °C = 4 - 20 mA)		●		
	Temperature of a Pt100 sensor positioned flexibly in chamber for external temperature monitoring (max. 3) - price per sensor (-20 to +70 °C = 4 - 20 mA)		●		
Fan speed monitoring with switching off the heating and with alarm in case of failure	V4		●		
Door with lock and key (safety lock)	B6		●		
Potential-free contact for combination error message (e.g. supply failure, sensor fault, fuse)	H6		●		
Door-open-recognition	V5		●		
MobileALERT, notification by SMS in case of any error or alarm of the device (requires option H6)	C3		●		

Accessories	110	260	450	750
Stainless steel grid, electropolished	E20165	E28891		E20182
Reinforced stainless steel grid, electropolished, max. loading 60 kg; from size 450 with guide bars and fixing screws (requires option K1). Please consider max. loading of chamber	E29767	E29766		B32190
Perforated stainless steel shelf	B00325	B29725		B00328
Reinforced stainless steel shelf, max. loading 60 kg; with guide bars and fixing screws (requires option K1). Please consider max. loading of chamber			-	B32191
Stainless steel slide-in drip tray, 15 mm rim, with guide bars and fixing screws (may affect the temperature distribution, requires option K1)			-	B32763
Stainless steel slide-in drip tray, 15 mm rim (may affect the temperature distribution, not in connection with option K1 for sizes 450/750)	E02073	E29726		E02075
Stainless steel bottom drip tray, 15 mm rim (may affect the temperature distribution, requires option K1)			-	B34055
Stainless steel bottom drip tray, 15 mm rim (may affect the temperature distribution, not in connection with option K1 for sizes 450/750)	B04359	B29722		B04362

Accessories Software and Connectivity	110	260	450	750
Software conforming to FDA AtmoCONTROL. Meets the requirements for the use of electronically stored data sets and electronic signatures as laid down in Regulation 21 CFR Part 11 of the US Food and Drug Administration (FDA). Respective IQ/OQ documents available in German and English language (without surcharge)			FDAQ1	
Integration of additional units (up to max. 31 units) into an already existent FDA-software licence			FDAQ2	
USB User-ID stick (with User-ID licence): Oven-linked authorisation licence (User-ID-programme) on Memory-stick, prevents undesired manipulation by unauthorised third parties. When reordering please specify serial number			B33170	
Ethernet connection cable 5 m for computer interface			E06189	
USB-Ethernet adapter			E06192	