

2 drawers

Minimum/maximum temperature memory

Forced-air cooling

potential-free contact/
RJ 45 socket by optional
PC-KIT-NET

Standalone or undercounter
installation

Antifreeze

Automatic defrosting

Visual and audible alarm
signal, even in the case
of power failure

Key switch

Digital temperature display

Condensate evaporation

Low-noise compressor

USB Port for reading out data



Low-noise compressor

Reduces noise to 40 dB (corresponds to noise level I; sounds perception: whisper).



Easy-to-clean ventilation slits

Large, smooth lamellas for easy cleaning of the ventilation slits.

BL 100

PRO-ACTIVE



according to DIN 58371

- **PRO-ACTIVE- Control:**
Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors
- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** positioned at the front to compensate for uneven floors.
- **Interior** made from impact-resistant, white plastic.
- **Interior consists** of two drawers on telescopic runners with stops. Stacking height: 19 cm.
- **Extra-thick 50-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door stop** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling**, switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic defrosting** with time limit and temperature monitoring.
- **Condensate evaporation** in the refrigerating machine room.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of power failure and temperature deviations. In the case of power failure, the monitoring unit remains in operation for approx. 30 hours on battery power. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using the floating contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.

Specification

Capacity	95 litres
Temperature setting	+4 °C
Voltage	220 – 240 V, 50/60 Hz
Power consumption	92 watts
Normal consumption	0.64 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	195 watts
Overall dimensions (including distance from wall)	w x d x h = 54 x 53.5 x 82 cm
Interior dimensions	w x d x h = 44 x 43 x 47 cm (usable width 2 cm, usable depth 5 cm, usable height 8 cm less)
Exterior dimensions with door open at 90°	w x d = 54 x 106 cm
Drawer inner dimensions	w x d x h = 37 x 32 x 8,5 cm
Max. load drawer	25 kg
Weight	Net weight 46 kg, gross weight 55 kg

Optional equipment

- **Glass door with lock.**
- **Tabletop** (exterior dimensions: 85 cm in height).
- **Decorative door frame** for attaching the customer's decorative plates (exterior dimensions: 55 cm in width).
- **Door fitting.**
- **Equipped with castors.**
- **Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
 - PC-KIT-NET
 - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body.
 - Disc-type pen recording thermometer, with 7-day measuring cycle, incorporated, with 100 recording discs and 5 felt tip pens.
 - Mechanical pen-recording thermometer with two waxed paper strips.