

# LABEX® 340 PRO-ACTIVE

Explosion protection - Zone 2

The interior is free of ignition sources

## Equipment

- 4 shelves
- 2 conductive drawers to prevent static charges
- Key switch
- Automatic defrosting
- Digital temperature display
- Forced-air cooling
- Comfortable access
- Potential-free contact
- Removable condensation container
- Antifreeze
- Visual and audible alarm signal
- Minimum/maximum temperature memory

**MADE IN  
GERMANY**



## PRO-ACTIVE-Features

- Faster response time in the event of impending faults thanks to proactive alarms
- Data recording can be read out via USB interface using a USB stick and software
- Minimisation of temperature deviations in the interior
- Maximum storage safety thanks to harmonised components



## LABEX®-Devices

Our LABEX® models are the safest explosion-proof devices on the market that offer maximum temperature stability.

### INTRINSIC SAFETY



#### Protected probes

The probes are protected via safety barriers



#### Explosion-proof fan

energy limiting power supply

### CONSTRUCTIVE SAFETY



#### Earthing concept

The user is grounded as soon as the door handle is touched. Static charge is discharged into the housing



#### No spark formation

caused by moving parts (shelves or conductive drawers)





# Explosion protection

Our promise - your safety!



KIRSCH was the first company in the laboratory cooling sector to adapt to the new ATEX product directive 2014/34/EU.

The interior of the devices is tested for absence of ignition sources by TÜV SÜD in conformity with Directive ATEX 2014/34/EU:

- All of the electrical equipment and components used in the interior (fans, temperature sensors, etc.) are specifically designed for use in zone 1\* and zone 2
- We also guarantee the maximum temperature stability in explosion-proof interiors
- Intrinsically safe supply to the temperature sensors in the interior
- Explosion-proof fan
- Special earthing concept for discharging electrical potential
- Plastic parts in the interior have an antistatic design

(depending on the model)

\*LABEX 465



## Liability according to ATEX operator- and product guidelines

According to the ATEX operating directive, the plant operator is responsible for the correct selection of the equipment. For the determination of the suitable EX zone (e.g. Zone 1, Zone 2), following explosion hazards, among other things, have to be taken into consideration: the explosiveness of the stored substances and the frequency of occurrence of an explosive atmosphere.


We will gladly assist you in selecting the correct explosion protected device and provide you with the technical report of the TÜV-SÜD. You will find the declaration of conformity on our website: [kirsch-medical.com/certificates/explosion-proofness](http://kirsch-medical.com/certificates/explosion-proofness).

# Compressor with inverter technology

- Environmentally friendly natural refrigerant R600a.  
Very low GWP value = 3 (Global Warming Potential)
- Reduction in power consumption by 35 % compared to the previous model (power consumption = 0.735 kWh/24h)
- Extended service life due to demand-orientated power adjustment
- Frequency: 50/60 Hz
- Low noise operation

If you need further support or have any questions, please contact us.

**info@kirsch-medical.de**  
**+49 (0)781 - 9227 0**



- **PRO-ACTIVE- Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations. World's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors.
- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** to compensate for uneven floors.
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior equipment** can be customised (surcharge may apply). See optional equipment.
- **Extra-thick energy saving insulation**, made from high-quality, compression-moulded and environmentally friendly material.
- **Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** switches off automatically when you open the door, ensures a uniform temperature and minimises temperature deviations.
- **Automatic defrosting** with time limit and temperature monitoring.
- **Removable condensation container.**
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory. Control and display sensors protected by safety barriers.
- **Power failure alarm** (visual and audible alarm), the monitoring unit remains in operation for approx. 30 hours on battery power.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations or other malfunctions. Door open alarm after 60 seconds.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional KIRSCH EVOLUTION CLOUD module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.
- **Antifreeze** against sub-zero temperatures.
- **Statically ventilated** refrigerating machine, hermetically sealed, energy saving, low noise, easy to service.
- **Low-noise compressor** reduces noise.

## Specification

Capacity	330 litres
Temperature setting	approx. 0 °C bis +15 °C
Voltage	220 - 240 V, 50 and 60 Hz
Power consumption	50.3 watts
Normal consumption	0.735 kWh / 24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	202 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 67 x 66 x 189 cm
Usable dimensions	w x d x h = 52.7 x 39 x 116 cm
Exterior dimensions with door open at 90°	w x d = 67 x 124 cm
Drawer/shelf size	w x d = 50.4 x 32 x 5.6 / 52.7 x 39 cm
Max. load drawer/shelf	16kg/40 kg
Weight (net/gross)	95 kg/109 kg
Temperature deviation	+/-0.66 °C
Noise emission	43.7 dB(A)

## Optional equipment

KIRSCH refrigerators and freezers offer numerous equipment options that can be retrofitted.



### Glass door

Transparency: Avoid unnecessary opening to check the contents. Lockable.



### Decorative frame

Made of stainless steel, allows to cover door with a decorative panel (thickness max. 2 mm).



### Plastic-drawer on roller runners

Up to 10 drawers in total are possible.



### Additional length and cross dividers

for the optimum organisation of your refrigerated goods.



### Door coupling

Connects the furniture door to the device door.



### Additional Shelves

Wire shelves, robust with load capacity up to 40 and 50 kg.



### Access Port

Simple insertion of an external temperature sensor with integrated cable feed-through.



### Castors


for easy handling and moving around.

## Accessories for temperature documentation




### PC-KIT-NET

Automatic temperature documentation and monitoring via your network (LAN connection).



### KIRSCH EVOLUTION CLOUD-Module

Maximum storage safety through optimal connectivity and real-time monitoring.



### External PT100/PT1000 with cold block

Additional temperature sensor for connection to existing/external monitoring system.



### Circular blade temperature recorder

Depending on the model, it is either installed in the machine compartment panel of the unit or integrated into an additional housing attachment.

\* For more information about our cloud, please contact us.



**Philipp Kirsch GmbH**

Im Lossenfeld 14  
77731 Willstätt  
Germany

Phone: +49 (0) 781 9227-0  
Telefax: +49 (0) 781 9227-200  
info@kirsch-medical.com

[www.kirsch-medical.com](http://www.kirsch-medical.com)



Photograph this QR code  
and learn  
about our entire  
product range.