



- Extensive Range
- 90+ Years of History
- Extended Aftercare Support
- UKAS Laboratory

Intellcold® Pharmacy Fridges

Bench Top RLDG0224

A next generation pharmacy refrigerator featuring the latest IntelliCold® 24-Range technology, designed for the safe storage of cold chain medicines in line with Public Health England guidance.

An enhanced IntelliCold® touch screen controller delivers accurate timekeeping, intelligent event logging and Bluetooth connectivity for fast access to temperature data via the Labcold Connect Android App. The flat, easy-clean controller locks automatically to prevent accidental changes.

Inside, three independent temperature probes provide advanced protection, including a low-temperature safeguard that prevents freezing. A pre-fitted simulated load has been carefully selected to represent the thermal behaviour of commonly stored pharmacy products. This ensures temperature readings reflect true product conditions, providing meaningful alarms when medicines are genuinely at risk; rather than masking excursions with oversized or unrepresentative loads.

Each unit is supplied with a FREE UK 5-year warranty for complete peace of mind. A UKAS temperature calibration certificate (Lab No. 8898) is available at an extra cost if required.

Specifications

| | |
|--------------------------------|-----------------|
| Product Code | RLDGO224 |
| Gross Capacity | 66 Litres |
| Style | Bench Top |
| UK Warranty | 5 Years |
| External Dimensions (mm) HxWxD | 735 x 450 x 310 |
| Internal Dimensions (mm) HxWxD | 588 x 331 x 226 |
| Temperature Range | 2°C to 8°C |
| Fridge Set Point | 5°C |









Specifications (cont.)

| | |
|---|---------------------|
| Internal Material | Moulded Plastic |
| External Material | Powder Coated Steel |
| Shelves | 3 |
| Net Weight | 34 Kg |
| Door Style | Glass |
| Lock Type | Key Lock |
| Digital Temperature Display | Yes |
| Digital Temperature Control | Yes |
| High/Low Temperature Alarm | Yes |
| Min/Max Temperature Recording | Yes |
| Integral Temp Data Logging | Yes |
| Automatic Temperature & Fridge Operation Data | Yes |
| Number of Temperature Probes | 3 |
| Internal Light | Yes |
| Self Closing Door | Yes |
| Door Open Alarm | Yes |
| Mains Failure Alarm | Yes |
| Alarm Battery Backup | Yes |
| Auto Defrost | Yes |
| Fan Assisted Cooling | Yes |
| Remote Alarm Contacts | Yes |
| Access Porthole | Yes |
| Access Porthole Size | 12mm |
| Power Consumption Kwh/24hrs | |
| Ambient Operating Temperature | 16°C to 32°C |

Features

- Fitted with the IntelliCold® touch screen controller
- 24/7 automatic temperature logging which is accessible via Bluetooth App
- Fan assisted cooling
- T3 Sensor & Low-Temperature Cut
- Controller and alarm battery back up
- Minimum/maximum temperature recording and display
- Auto defrost
- Self-closing door
- Remote alarm contacts
- Compliant with all leading professional guidelines
- FREE five-year labour warranty
- Event based logging
- Door lock with two keys
- Realistic pre-fitted simulated Load
- High/Low temperature alarm
- Door open and power failure alarm
- Access port for additional monitoring equipment
- Internal light
- Brackets for wall mounting

Models

| | Model | Gross Capacity | Door Style | Lock Type |
|--|----------------------------|----------------|------------|--------------|
|  | Bench Top RLDF0119 Diglock | 36 litres | Solid | Digital Lock |
|  | Bench Top RLDG0119 Diglock | 36 litres | Glass | Digital Lock |
|  | Bench Top RLDG0219 Diglock | 66 litres | Glass | Digital Lock |
|  | Bench Top RLDF0224 | 66 Litres | Solid | Key Lock |
|  | Bench Top RLDF0224DIGLOCK | 66 Litres | Solid | Digital Lock |
|  | Bench Top RLDF0124 | 36 litres | Solid | Key lock |
|  | Bench Top RLDG0124 | 36 litres | Glass | Key Lock |
|  | Bench Top RLDG0224 | 66 Litres | Glass | Key Lock |