



# NBV series




### **NBV 15 SL**

### **DIRECT RADIATION UV-C GERMICIDAL LAMP**

## HOW DOES THE DIRECT RADIATION UV-C GERMICIDAL LAMP WORK?

Direct radiation germicidal lamps type NBV are designed to prevent primary and secondary infections of patients and medical personel caused by airborne pathogenic microorganisms (pathogens). Using direct germicidal radiation in the rooms where infected patients or patients with immune deficiencies are staying, significantly reduces the probability of infection spread by air. Raising the level of microbiological purity of the air and the rooms helps to destroy and reduce impact of existing outbreaks of pathogens.



CLEAN AIR AND SURFACE

### **BASIC DATA:**

BASIC DATA:	
Air flow disinfection function (flow disinfection chamber)	no
Direct radiation function	yes
Presence of people, animals, plants inside the room during disinfection process	not allowed
Mounting type	ceiling-mounted
Working time counter	yes, internal digital counter with acoustic signalling, without the display
External bulbs	yes, 1 bulb
Casing material	powder laquered aluminium
Reflector material	high quality reflective aluminium
Switch on/off	no
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes





### **TECHNICAL DATA SHEET**

### **NBV** series

### **NBV 15 SL**

### **DIRECT RADIATION UV-C GERMICIDAL LAMP**

### **TECHNICAL DATA:**


Supply voltage	230 V, 50 Hz
Power consumption	18 W
UV-C bulbs (Philips/Osram)	1 x 15 W (TUV/HNS)
UV-C radiation wave-length	253,7 nm
Useful lifetime of the UV-C bulbs	min. 8000 h
Radiation intensity of the external UV-C tube at the distance of 1m	0,9 W/m <sup>2</sup>
Effective area of the lamp	6-8 m <sup>2</sup>
Exposure angle adjustment range	240°
Anti-shock protection class	I .
Ingress Protection Code	IP 20
Lamp body dimensions	500 x 85 x 135 mm
Total lamp mass	3,5 kg
Extension arm (holder) length:	50,0 cm
Power cord length	0,8 m

### **APPLICATION RECOMMENDATIONS:**

### Hospitals

- operation theatres
- intensive care units
- emergency rooms
- examination and treatment rooms
- reception units
- patient rooms, isolation rooms
- soiled/dirty utility rooms

Outpatient clinics Medical laboratories Chemist's Beauty salons Pharmaceutical industry Food industry Cosmetic industry



Ultra-Viol's realisation



Digital counter with acoustic signalling, without the display