



Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland TIN PL 727 00 21 903 www.ultraviol.pl/en

SURFACE

B

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 601 94 76 67 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET NBV series

DIRECT RADIATION

NBV 30 PLW DIRECT RADIATION UV-C GERMICIDAL LAMP

HOW DOES THE DIRECT RADIATION **UV-C GERMICIDAL LAMP WORK?**

r Direct radiation germicidal lamps type NBV are designed to prevent primary and secondary infections of patients and medical personel caused by airborne pathogenic microorganisms (pathogens). Using direct germicidal radiation in the rooms where infected patients or patients with immune deficiencies are staying, significantly reduces the probability of infection spread by air. Raising the level of microbiological purity of the air and the rooms helps to destroy and reduce impact of existing outbreaks of pathogens.



BASIC DATA:

| no |
|---|
| yes |
| not allowed |
| on mobile stand |
| yes, digital working time counter with 4-field LED display and acoustic signalling |
| yes, 1 bulb |
| powder laquered aluminium |
| high quality reflective aluminium |
| built in lamp body |
| +10°C to +40°C |
| 30% to 70% |
| 700 hPa to 1060 hPa |
| |
| yes |
| |





Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland TIN PL 727 00 21 903 www.ultraviol.pl/en

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 601 94 76 67 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET

NBV series

NBV 30 PLW

DIRECT RADIATION UV-C GERMICIDAL LAMP

TECHNICAL DATA:

| Supply voltage | 230 V, 50 Hz |
|---|-----------------------------------|
| Power consumption | 33 W |
| UV-C bulbs (Philips/Osram) | 1 x 30 W (TUV/HNS) |
| UV-C radiation wave-length | 253,7 nm |
| Useful lifetime of the UV-C bulbs | min. 8000 h |
| Radiation intensity of the external UV-C tube at the distance of 1m | 2,3 W/m ² |
| Effective area of the lamp | 12-15m ² |
| Exposure angle adjustment range | 240° |
| Anti-shock protection class | I |
| Ingress Protection Code | IP 20 |
| Operation mode | continuous |
| Lamp body dimensions | 960 x 85 x 135 mm |
| Total lamp mass | 8,5 kg |
| Height of the stand | 180,0 cm |
| Power cord length | 3,0 m, ended with the socket plug |
| | |

APPLICATION RECOMMENDATIONS:

Hospitals

- operation theatres
- intensive care units
- emergency rooms
- examination and treatment rooms
- reception units
- patient rooms, isolation rooms
- soiled/dirty utility rooms

Outpatient clinics Medical laboratories Chemist's Beauty salons Pharmaceutical industry Food industry Cosmetic industry



Ultra-Viol's realisation