



Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland TIN PL 727 00 21 903 www.ultraviol.pl/en Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 601 94 76 67 fax +48 42 715 02 16, e-mail: office@ultraviol.pl


TECHNICAL DATA SHEET **NBV series**



NBV 15 N DIRECT RADIATION UV-C GERMICIDAL LAMP

HOW DOES THE DIRECT RADIATION UV-C GERMICIDAL LAMP WORK?

Direct radiation germicidal lamps type NBV are designed to prevent primary and secondary infections of patients and medical personel caused by airborne pathogenic microorganisms (pathogens). Using direct germicidal radiation in the rooms where infected patients or patients with immune deficiencies are staying, significantly reduces the probability of infection spread by air. Raising the level of microbiological purity of the air and the rooms helps to destroy and reduce impact of existing outbreaks of pathogens.



CLEAN AIR AND SURFACE

BASIC DATA:

r flow disinfection function ow disinfection chamber)	no
rect radiation function	yes
esence of people, animals, plants side the room during disinfection process	not allowed
ounting type	wall-mounted
'orking time counter	no
ternal bulbs	yes, 1 bulb
asing material	powder laquered aluminium
eflector material	high quality reflective aluminium
vitch on/off	no
nbient temperature	+10°C to +40°C
elative humidity	30% to 70%
mospheric pressure	700 hPa to 1060 hPa
eclaration of conformity	yes
ser's manual English version	yes
	yes





Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland TIN PL 727 00 21 903 www.ultraviol.pl/en

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 601 94 76 67 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET

NBV series

NBV 15 N

DIRECT RADIATION UV-C GERMICIDAL LAMP

TECHNICAL DATA:

Supply voltage	230 V, 50 Hz
Power consumption	18 W
UV-C bulbs (Philips/Osram)	1 x 15 W (TUV/HNS)
UV-C radiation wave-length	253,7 nm
Useful lifetime of the UV-C bulbs	min. 8000 h
Radiation intensity of the external UV-C tube at the distance of $1 m$	0,9 W/m ²
Effective area of the lamp	6-8 m ²
Exposure angle adjustment range	160°
Anti-shock protection class	I
Ingress Protection Code	IP 20
Operation mode	continuous
Lamp body dimensions	500 x 85 x 135 mm
Total lamp mass	2,4 kg
Holder length	12,0 cm
Power cord length	0,8 m

APPLICATION RECOMMENDATIONS:

Hospitals

- operation theatres
- intensive care units
- emergency rooms
- examination and treatment rooms
- reception units
- patient rooms, isolation rooms
- soiled/dirty utility rooms

Outpatient clinics Medical laboratories Chemist's Beauty salons Pharmaceutical industry Food industry Cosmetic industry



Ultra-Viol's realisation