

## VELP Scientifica Solutions for Incubation



**FTC 120**



**FOC 120E Connect**



**FOC 200E Connect**



**FOC 120I Connect**



**FOC 200I Connect**



**FOC 200IL Connect**

Internal transparent door				•	•	•
Total volume L	120	109	169	109	169	169
Temperature settings °C	20, constant	from 3 to 50	from 3 to 50	from 3 to 50	from 3 to 50	from 3 to 50
Temperature stability and homogeneity °C	± 0.5	± 0.5	± 0.5	± 0.5	± 0.5	± 0.5
Timer						controls lighting cycles
Lighting system						LED
Ermes connection		•	•	•	•	•
TEMPSoft™ connection		•	•	•	•	•
Interfaces		Wi-Fi, 2 x RS485	Wi-Fi, 2 x RS485	Wi-Fi, 2 x RS485	Wi-Fi, 2 x RS485	Wi-Fi, 2 x RS485
Electronic thermoregulation system	Traditional	Auto-Tuning	Auto-Tuning	Auto-Tuning	Auto-Tuning	Auto-Tuning
Number of shelves supplied	2	2	3	2	3	3 (2 illuminated)
Maximum number of shelves	4	4	5	4	5	5
Internal socket	2	2	2	2	2	2
Capacity (BOD System)	3 x BOD (EVO) Sensor System 6	3 x BOD (EVO) Sensor System 6	4 x BOD (EVO) Sensor System 6	2 x BOD (EVO) Sensor System 6	4 x BOD (EVO) Sensor System 6	4 x BOD (EVO) Sensor System 6
	2 x BOD Sensor System 10	2 x BOD Sensor System 10	2 x BOD Sensor System 10	1 x BOD Sensor System 10	1 x BOD Sensor System 10	1 x BOD Sensor System 10
Dimensions (WxHxD) mm	540x905x550	540x912x550	540x1263x550	540x912x550	540x1263x600	540x1300x550
	(21.3x35.6x21.7)	(21.3x35.9x21.7)	(21.3x49.7x21.7)	(21.3x35.9x21.7)	(21.3x49.7x21.7)	(21.3x51.2x21.7)
Weight	36.0	36.0	46.3	36.0	46.3	50.0
	(79.4)	(79.4)	(102.1)	(79.4)	(102.1)	(110.2)
Power Supply	230 V	230 V	230 V	230 V	230 V	230 V
Power	120 W	120 W	400 W	120 W	400 W	400 W