

Precision incubator

Model IN110plus



Standard equipment

Ventilation and Control

- natural convection
- adjustment of pre-heated fresh air admixture by air flap control in 10% steps for each segment individually
- vent connection with restrictor flap
- adaptive multifunctional digital PID-microprocessor controller with 2 high-definition TFT-colour displays
- self-diagnostics for fault analysis
- 2 Pt100 sensors Class A in 4-wire-circuit, mutually monitoring and taking over the performance at the same temperature value
- digital timer adjustable from 1 minute to 99 days, 23 hours
- parameters adjustable on ControlCOCKPIT: temperature (Celsius or Fahrenheit), air flap position, programme time, time zones, summertime/wintertime
- SetpointWAIT function - the process time does not start until the set temperature is reached
- HeatBALANCE function for adapting the distribution of the heating performance of the upper and lower heating circuit from -50% to +50%
- Setting of languages on ControlCOCKPIT: German/English/Spanish/French
- resolution of display for setpoint values 0.1 °C up to 99.9 °C, 0.5 °C from 100 °C and for actual values 0.1 °C (LED)
- calibration facility directly at ControlCOCKPIT for three freely selectable temperature values

- programme stored in case of power failure
- fixed sterilisation programme (4 hours/160 °C) for sterilisation of working chamber, adjustable on display
- incl. works calibration certificate for +37 °C

Multiple Overtemperature Protection

- with audible and visual alarm
- overtemperature monitor TWW, protection class 3.1 or adjustable temperature limiter TWB, protection class 2, selectable on display
- mechanical temperature limiter TB, protection class 1 according to DIN 12 880
- additionally integrated over- and undertemperature monitor "ASF", automatically following the setpoint value at a preset tolerance range; alarm in case of over- or undertemperature, heating is switched off in case of overtemperature
- mechanical temperature limiter TB, protection class 1 according to DIN 12 880 to switch off the heating approx. 10 °C above nominal temperature

Textured Stainless Steel Casing

- w x h x d: 745 x 867 x 584 mm
- fully insulated stainless steel door with 2-point locking (compression door lock)
- inner glass door
- rear zinc-plated steel

Interior - Heating Concept

- w x h x d: 560 x 480 x 400 mm, 108 l

- easy-to-clean interior,made of stainless steel,reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides
- 2 stainless steel grids

Temperature Range

- min. 5°C above ambient up to +80°C

Voltage / Power Rating

- 230 V (+/- 10%), 50/60 Hz
- ca. 1.400 W

Packing Data

- net weight approx. 74 kg
- gross weight carton approx. 88 kg

- dimensions approx.:
carton w x h x d: 85 x 114 x 79 cm
- the appliances must be transported upright

Customs Tariff Number

- 8419 8998

Country of Origin

- Federal Republic of Germany

WEEE-Reg.-No.

- DE 66812464