

Laminar-flow cabinet BIO130 type A2

🏠 [Laminar airflow Safety class II > Laminar-flow cabinet BIO130 A2](#)



Description

- vertical laminar air flow
- 2 HEPA filters with efficiency of 99.995% for MPPS
- microprocessor control system with touchscreen display in Polish/English or any other language
- automatic filter compensation ensures constant and safe speed of air flow in the cabinet
- hour timer of the cabinet and UV lamp operation
- adjusted air flow
- clear and easy-to-use control panel with optical and acoustic signals
- silent fans, noise level below 56 dB
- front window made of tempered double glass without frame, inclined at an angle of 8°, electrically raised and lowered, with a possibility to shut it completely – closing the workspace
- split worktop (4 autoclavable boards), made of stainless steel
- internal workspace made of stainless steel
- permanently fixed UV lamp in the upper part of the workspace, protected from accidental switching on during operation
- white LED lightning system min. 1200 lux
- workspace sides with window openings
- two power sockets inside workspace
- removable armrest
- frame with lockable castors
- power supply 230V/60 Hz

Gallery



Warranty and certificates

Product and manufacturer certificates:

- TUV certificate for compliance with the standard EN 12469, EN 61010-1:2010, EN 61326-1:2013
- CE declaration of the manufacturer
- ISO 9001



Protocol from tests in laboratory is issued and enclosed for each cabinet.

Warranty for the laminar airflow unit: 36-month warranty.





Nominal width in mm	1340	
External dimensions width/depth/height in mm	1333 / 790 / 2069	
Internal dimensions width/depth/height in mm	1266 / 644 / 710	
Area of working space in m ²	0,81	
Number of perforated plates in top in pcs.	4	
Maximum height of window panel lifting during work in mm	200	
Maximum height of front window panel lifting in mm	440	
Air flow in m/s	inlet	0,53
	working space	0,35
Air flow in m ³ /h	inlet	376
	operation 63%	761
	outlet 37%	376
Number of filters HEPA or ULPA in pcs.	preliminary	-
	main	1
	outlet	1
Filter efficiency	> 99,995 % for MPPS - H14	
Loudness level in dB	< 56	
Illuminance in lux	> 1200	
Maximum power consumption in W	400	
Power of UV bactericidal lamp in W	18	
Number of electric sockets inside the chamber standard, in pcs.	2	
Control panel with touchscreen	menu in Polish, English or other language	
Gas valve (option)	mechanical, with 3/8" connector	
Chamber construction	Floor, working plates, sides and back of the working space	Steel sheet AISI 304(1.403). Acid-proof, galvanized steel sheet
	Body	Steel 1203, thickness 1,5 mm, powder coated RAL 7035
	Front window panel	Safety glass, thickness 6 mm, inclined at an angle of 8°
Equipment weight in kg	260	

In the interest of continued product development, ALPINA reserves the right to make improvements in this leaflet and the products it describes at any time, without notices or obligation. Colors of products may not be perfectly accurate due to variations caused by photograph, printing method or monitor settings.

