



BOECO MINI CENTRIFUGE M-6

this Mini-centrifuge is ideal for quick spin downs for Micro and PCR tubes and PCR strip. The M-6 is supplied with a 6 x 1,5/2,0ml angle rotor, a 2x8x0,2ml strip rotor and a slide rotor.

Operation of the centrifuge begins when the lid is closed. When opening the lid the rotor automatically decelerates and comes to a stop.

A Rubber footplate keeps the unit stable and avoids vibration.

The M-6 is CE marked and has been manufactured under ISO 9001

Technical details

Max. RPM (speed) / RCF:	6.000 rpm / 2000 x g
Noise level:	50 dB(A)
Power:	120V to 240V, 50/60Hz
Dimensions in mm:	175 (D) x 148 (W) x 118 (H)
Net weight:	approx 1,1 kg

Code	Description
BOE 8074000	BOECO Mini Centrifuge M-6, EU Plug
BOE 8074100	BOECO Mini Centrifuge M-6, US Plug
BOE 8074200	BOECO Mini Centrifuge M-6, UK Plug

BOECO CENTRIFUGE MICROSPIN 12

is a compact bench-top microliter centrifuge for medical and biological research; molecular diagnostics, biochemistry, immunology and cell technologies. It can be used for extracting RNA/DNA samples, separation of cell suspensions and other micro quantitative analyses.

The microprocessor control provides precise control of the set parameters and a user-friendly interface allows a easy entry of parameters.

The brushless motor provides quite, vibration free performance, even at high speeds and a long product service life.

The angle rotor is made out of aluminium.

Due to the low voltage external power supply, the Microspin 12 can be used in cold rooms.

Controls and displays

- ▶ During centrifugation the actual values of the parameters are indicated
- ▶ Entry of the running parameters via foil keypad
- ▶ Speed display in RPM x 100, increment 100 rpm
- ▶ Time t/ min: 1 - 30 min, increment 1 min
- ▶ Open lid key

Safety

- ▶ Lid locking and holding device
- ▶ Emergency lid lock release
- ▶ Metal protective inserts and enclosures inside the body
- ▶ See-through glass in the lid
- ▶ Imbalance switch-off

The Microspin 12 conforms to safety regulations such as EN 61326, EN 61010 or the CE mark and all relevant EC standards and DIN norms and has been manufactured under ISO 9001:2000

Technical details

Max. RPM (speed) / RCF:	12.000 rpm / 8490 RCF
Noise level:	≤ 57 dB(A)
Power (external):	AC 100-240V, 60W/DC24V, 2.1A
Dimensions in mm:	200 (D) x 240 (W) x 125 (H)
Net weight:	approx 3,5 kg

Code	Description
BOE 8075000	BOECO Micro centrifuge Microspin M-12, 100-240V, 50/60 Hz, with angle rotor for 12 x 1,5/2,0 ml tubes and each 12 adapters for 0,2 and 0,5 ml tubes

